§ 63.8990

(b) An HCl production facility is not subject to this subpart if it is also subject to NESHAP under one of the subparts listed in paragraphs (b)(1) through (5) of this section.

(1) 40 CFR part 63, subpart S, National Emission Standards for Hazardous Air Pollutants from the Pulp

and Paper Industry.

(2) 40 CFR part 63, subpart CCC, National Emission Standards for Hazardous Air Pollutants for Steel Pickling-HCl Process Facilities and Hydrochloric Acid Regeneration Plants.

(3) 40 CFR part 63, subpart MMM, National Emission Standards for Hazardous Air Pollutants for Pesticide Ac-

tive Ingredient Production.

- (4) 40 CFR part 63, subpart EEE, National Emission Standards for Hazardous Air Pollutants for Hazardous Waste Combustors.
- (5) 40 CFR part 63, subpart GGG, National Emission Standards for Pharmaceuticals Production.
- (c) An HCl production facility is not subject to this subpart if it is located following incineration the chlorinated waste gas streams, waste liquids, or solid wastes, and the emissions from the HCl production facility are subject to one of the requirements listed in paragraphs (c)(1) through (3) of this section.
- (1) Section 63.113(c), subpart G, National Emission Standards for Organic Hazardous Air Pollutants from the Synthetic Organic Chemical Manufacturing Industry for Process Vents, Storage Vessels, Transfer Operations, and Wastewater.
- (2) Section 264.343(b), Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities (subpart O, Incinerators)
- (3) Section 266.107, subpart H, Burning of Hazardous Waste in Boilers and Industrial Furnaces.
- (d) An HCl production facility is not subject to this subpart if it produces HCl through the direct synthesis of hydrogen and chlorine and is part of a chlor-alkali facility
- (e) An HCl production facility is not subject to this subpart if it is a research and development facility.
- (f) An HCl production facility is not subject to this subpart if all of the gas-

eous streams containing HCl and chlorine (Cl₂) from HCl process vents, HCl storage tanks, and HCl transfer operations are recycled or routed to another process prior to being discharged to the atmosphere.

§63.8990 What parts of my plant does this subpart cover?

- (a) This subpart applies to each new, reconstructed, or existing affected source at an HCl production facility.
- (b) The affected source is the group of one or more HCl production facilities at a plant site that are subject to this subpart, and all associated wastewater operations, which contain the collection of emission streams listed in paragraphs (b)(1) through (5) of this section.

(1) Each emission stream from an HCl process vent.

- (2) Each emission stream from an HCl storage tank.
- (3) Each emission stream from an HCl transfer operation.
- (4) Each emission stream resulting from leaks from equipment in HCl/Cl₂ service.
- (5) Each emission stream from HCl wastewater operations. There are no emission limitations or other requirements in this subpart that apply to HCl wastewater operations.
- (c) An affected source is a new affected source if you commenced construction of the affected source after September 18, 2001 and you met the applicability criteria of §63.8985 at the time you commenced construction.
- (d) An affected source is reconstructed if you meet the criteria as defined in §63.2.
- (e) An affected source is existing if it is not new or reconstructed.

§63.8995 When do I have to comply with this subpart?

- (a) If you have a new or reconstructed affected source, you must comply with this subpart according to paragraphs (a)(1) or (2) of this section.
- (1) If you start up your affected source before April 17, 2003, you must comply with the emission limitations and work practice standards in this subpart no later than April 17, 2003.
- (2) If you start up your affected source after April 17, 2003, you must comply with the emission limitations

and work practice standards in this subpart upon startup of your affected source.

- (b) If you have an existing affected source, you must comply with the emission limitations and work practice standards no later than 3 years after April 17, 2003.
- (c) If you have an area source that increases its emissions or its potential to emit such that it becomes a major source of HAP, the provisions in paragraphs (c)(1) and (2) of this section apply.
- (1) Any portion of the existing facility that is a new affected source or a new reconstructed source must be in compliance with this subpart upon startup.
- (2) All other parts of the source must be in compliance with this subpart no later than the date 3 years after the area source becomes a major source.
- (d) You must meet the notification requirements in §63.9045 according to the schedule in §63.9045 and in subpart A of this part. Some of the notifications must be submitted before you are required to comply with the emission limitations in this subpart.

EMISSION LIMITATIONS AND WORK PRACTICE STANDARDS

§ 63.9000 What emission limitations and work practice standards must I meet?

- (a) With the exceptions noted in paragraph (c) of this section, you must meet the applicable emission limit and work practice standard in Table 1 to this subpart for each emission stream listed under §63.8990(b)(1) through (4) that is part of your affected source.
- (b) With the exceptions noted in paragraph (c) of this section, you must meet the applicable operating limit in Table 2 to this subpart for each emission stream listed under §63.8990(b)(1) through (3) that is part of your affected source.
- (c) The emission streams listed in paragraphs (c)(1) through (3) of this section are exempt from the emission limitations, work practice standards, and all other requirements of this subpart.
- (1) Emission streams from HCl storage tanks that never store liquid HCl

product with a concentration of 30 weight percent or greater.

- (2) Emission streams from HCl transfer operations that never load liquid HCl product with a concentration of 30 weight percent or greater.
- (3) Emission streams from HCl wastewater operations.

GENERAL COMPLIANCE REQUIREMENTS

§ 63.9005 What are my general requirements for complying with this subpart?

- (a) You must be in compliance with the emission limitations and work practice standards in this subpart at all times, except during periods of startup, shutdown, and malfunction.
- (b) You must always operate and maintain your affected source, including air pollution control and monitoring equipment, according to the provisions in §63.6(e)(1)(i).
- (c) You must develop and implement a written startup, shutdown, and malfunction plan according to the provisions in \$63.6(e)(3).
- (d) All monitoring equipment shall be installed, calibrated, maintained, and operated according to manufacturer's specifications or other written procedures that provide adequate assurance that the equipment would reasonably be expected to monitor accurately. For each monitoring system required in this section, you must develop, implement, and submit to the Administrator a site-specific monitoring plan that addresses the installation requirements in paragraphs (d)(1) through (3) of this section, the ongoing procedures in paragraphs (d)(4) through (6) of this section, and the requirements in §63.9025, as applicable. You must submit the plan with your Notification of Compliance Status. Upon request of the Administrator, you must promptly correct any deficiencies in a site-specific monitoring plan and submit the revised plan.
- (1) Installation of the continuous monitoring system (CMS) sampling probe or other interface at a measurement location relative to each affected process unit such that the measurement is representative of control of the exhaust emissions (e.g., on or downstream of the last control device).